


Bravo

MORE THAN A COMPLIMENT



Up to 17.0 SEER2 Rating



12K, 18K & 24K Btu/h

SINGLE-ZONE WALL MOUNTED
MINI SPLIT AIR CONDITIONING SYSTEM



Use your Smart device to
control your unit from
anywhere with
SMART APP!



Features:

- Remote Control Included
- Smart App: Connect from anywhere
- Comfortable Sleep Mode
- Super Mode
- Eco Mode
- Multiple Fan Speeds
- Timer
- Sleep Mode
- Louver Auto Swing
- Anti-Mildew Mode
- LED Display



Indoor Model		BRV-12W-115VI	BRV-18W-230VI	BRV-24W-230VI	
Outdoor Model		BRV-12LS-115VO	BRV-18LS-230VO	BRV-24LS-230VO	
Power Supply	V-Ph-Hz	115V-1Ph-60	208/230V-1Ph-60	208/230V-1Ph-60	
Cooling	Capacity	Btu/h	11000	16500	22000
	EER2	Btu/h	8.50	8.50	8.85
	SEER2	Btu/h	17.0	17.0	17.0
Heating	Rated Capacity	Btu/h	11500	17000	22000
	HSPF2-4	Btu/h	8.0	8.5	8.0
	COP2	W/W	3.0	3.0	3.0
Minimum Circuit Ampacity	A	16	13	14	
Max Fuse	A	25	20	20	
Indoor Air Flow	CFM	294/265/235	559/471/382	765/647/588	
Indoor Noise Level (Hi/Mi/Lo)	dB(A)	38/34/30	43/38/33	49/45/41	
Indoor Unit	Dimensions (WxDxH)	in	30.59x9.84x7.91	35.83x11.57x8.11	39.76x12.40x8.66
	Packing (WxDxH)	in	33.07x12.40x10.24	38.54x14.65x10.91	43.15x15.35x11.69
	Net Weight	lbs	17.6	22.0	28.7
Outdoor Air Flow	CFM	1213	1704	1645	
Outdoor Side Noise Level	dB(A)	52	52	55	
Outdoor Unit	Dimensions (WxDxH)	in	30.59x11.42x19.61	33.58x13.74x23.70	33.58x13.74x23.70
	Packing (WxDxH)	in	32.20x12.80x20.47	35.04x15.16x24.72	35.04x15.16x24.72
	Net Weight	in	51.8	63.9	72.8
Refrigerant Type/Quantity	oz	R410A/22.6	R410A/37.4	R410A/48.3	
Refrigerant Precharge	ft	25	25	25	
Design Pressure	PSIG	652.5	652.5	652.5	
Refrigerant Piping	Liquid Side / Gas Side	in	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"
	Max Refrigerant Pipe Length	ft	50	65	65
Connection Wiring	Size x Core Number		4*16AWG	4*16AWG	4*16AWG
Ambient Temperature	Indoor (Cooling/Heating)	°F	>=62/<=86	>=62/<=86	>=62/<=86
	Outdoor (Cooling/Heating)	°F	5~122/-4~86	5~122/-4~86	5~122/-4~86

