

Bravo

MORE THAN A COMPLIMENT





Bravo's SMART APP allows you to control your units at home through your smart devices from anywhere.



Bravo

MORE THAN A COMPLIMENT

ABOUT THE COMPANY

Discover BRAVO, the latest addition to the portfolio of one of the world's leading HVAC manufacturers, renowned for its expansive global presence. BRAVO, now making its mark in the North American market, encapsulates the essence of Italian design while embracing the latest European trends. In its slogan, "More Than a Compliment", BRAVO reflects its commitment to surpassing expectations with superior quality and efficiency. In the United States, BRAVO is proudly distributed by COMFORTSIDE, LLC, a seasoned distributor with a decade of expertise in bringing top-tier air conditioning brands to consumers. Explore the exceptional offerings of BRAVO for a blend of style and performance in HVAC solutions.





CONTENTS:



SINGLE-ZONE WALL MOUNTS

6-7



SINGLE-ZONE DUCTS & CEILING CASSETTES

8-11



SINGLE-ZONE MULTI-POSITION AIR HANDLER

12-13



MULTI-ZONE DUCTS & CEILING CASSETTES

14-17

MULTI-ZONE COMBINATION CHART

18-19



Up to 17.0 SEER2 Rating



SINGLE-ZONE

MINI SPLIT AIR CONDITIONING SYSTEM

12K, 18K, 24K & 36K Btu/h



Use your Smart device to control your unit from anywhere with SMART APP!



Features:

- Remote Control Included
- Smart App: Connect from anywhere
- Comfortable Sleep Mode
- Super Mode
- Eco Mode
- Multiple Fan Speeds
- Timer
- Louver Auto Swing
- Anti-Mildew Mode
- LED Display



13' Line Sets and Communication Cable included



Indoor Model			BRV-R12W-115VI	BRV-R12W-230VI	BRV-R18W-230VI	BRV-R24W-230VI	BRV-R36W-230VI
Outdoor Model			BRV-R12LS-115VO	BRV-R12LS-230VO	BRV-R18LS-230VO	BRV-R24LS-230VO	BRV-R36LS-230VO
Power Supply	V-Ph-Hz		115-1-60	208/230-1-60	208/230-1-60	208/230-1-60	208/230-1-60
Cooling	Rated Capacity	Btu/h	12,000	12,000	17,000	24,000	35,000
	EER2	Btu/h	9.5	9.5	9.5	9.5	9.5
	SEER2	Btu/h	17	17	17	17	17
Heating	Rated Capacity	Btu/h	12,000	12,000	17,000	24,000	34,500
	HSPF2-4	Btu/h	9.0	9.0	10.5	8.64	8.5
	COP2	W/W	3.5	3.2	3.5	3.5	3.2
Minimum Circuit Ampacity	A		17	11	13	13	23
Max Fuse	A		25	15	20	20	35
Indoor Air Flow (Turbo/Hi/Mi/Lo/Mute)	CFM		276/265/241/224/206	294/264/235/206/159	412/364/294/235/208	676/629/505/412/352	882/741/564/458/411
Indoor Noise Level (Turbo/Hi/Mi/Lo/Mute)	dB(A)		42.9/40/36.1/33/29	45/42/39/35/33	49/45/43/40/37	47/45/39/34/32	55/52/46/41/39
Indoor Unit	Dimensions (WxDxH)	in	30.59x7.91x9.84	30.59x7.91x9.84	35.82x8.11x11.57	39.76x8.66x12.40	46.88x10.15x14.17
	Packing (WxDxH)	in	33.07x12.4x10.23	33.07x12.40x10.23	38.54x14.64x10.90	43.15x15.35x11.81	49.60x16.92x12.91
	Net Weight	lbs	16.5	16.5	20.9	26.5	38.6
Outdoor Air Flow	CFM		276/265/241/224/206	294/264/235/206/159	412/364/294/235/208	676/629/505/412/352	882/741/564/458/411
Outdoor Side Noise Level	dB(A)		53	55	57	55	63
Outdoor Unit	Dimensions (WxDxH)	in	30.59x11.42x19.61	30.59x11.41x19.61	31.88x12.00x21.61	30.70x13.74x23.81	38.50x16.57x31.61
	Packing (WxDxH)	in	32.99x13.30x21.25	32.99x13.30x21.25	33.54x14.09x24.02	35.43x15.94x25.39	40.23x18.89x32.87
	Gross Weight	lbs.	54.01	52.91	61.73	74.96	105.8
Refrigerant Type	oz		R32	R32	R32	R32	R32
Refrigerant Precharge	ft		25	25	25	25	25
Design Pressure	PSIG		725.18	725.18	725.18	725.18	725.18
Refrigerant Piping	Liquid Side / Gas Side	in	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	1/4" / 5/8"
	Max Refrigerant Pipe Length	ft	50	50	50	65	65
Connection Wiring	Size x Core Number		4x16AWG	4x16AWG	4x16AWG	4x16AWG	4x16AWG
Ambient Temperature	Indoor (Cooling/Heating)	°F	>=62/<=86	>=62/<=86	>=62/<=86	>=62/<=86	>=62/<=86
	Outdoor (Cooling/Heating)	°F	5~122/-4~86	5~122/-4~86	5~122/-4~86	5~122/-4~86	5~122/-4~86





Up to 20.0 SEER2 Rating



SINGLE-ZONE

CEILING CASSETTE MINI SPLIT SYSTEM

9K, 12K, 18K & 24K Btu/h




Use your Smart device to control your unit from anywhere with SMART APP!



(Panel Sold Separately)

BRV-PNL09-18CT
25.59×25.59×1.18 in.
Panel Net Weight: 6.0 lb



BRV-PNL24CT
37.4×37.4×1.3 in.
Panel Net Weight: 13.2 lb



16' Line Set and Drain Lines,
21' Communication Cable Included

Wall Thermostat included with Ceiling Cassette Unit



Indoor Model			BRV-P09CT-230VI	BRV-P12CT-230VI	BRV-P18CT-230VI	BRV-P24CT-230VI
Panel Model			BRV-PNL09-18CT	BRV-PNL09-18CT	BRV-PNL09-18CT	BRV-P24CT-230VI
Outdoor Model			BRV-P09LS-230VO	BRV-P12LS-230VO	BRV-P18LS-230VO	BRV-P24LS-230VO
Power Supply			V-Ph-Hz	208~230-1-60	208~230-1-60	208~230-1-60
Cooling	Rated Capacity	Btu/h	9,000	12,000	18,000	24,000
	EER2	Btu/h	11.0	9.5	9.5	9.5
	SEER2	Btu/h	20.0	20.0	20.0	20.0
Heating	Rated Capacity	Btu/h	9,000	12,000	18,500	24,000
	HSPF2-4	Btu/h	9.5	9.5	9.5	9.5
	COP2	W/W	3.8	3.5	2.9	3.5
Minimum Circuit Ampacity			A	10	11	12
Max Fuse			A	15	15	20
Indoor Air Flow (Turbo/Hi/Mi/Lo/Mute)			CFM	329/300/270/217/194	360/320/260/200/190	441/394/335/282/253
Indoor Noise Level (Turbo/Hi/Mi/Lo/Mute)			dB(A)	43/41/37/33/32	45/43/39/35/32	48/46/42/39/37
Indoor Unit	Dimensions (WxDxH)	in	22.44×22.44×10.24	22.44×22.44×10.24	22.44×22.44×10.24	32.99×32.99×10
	Packing (WxDxH)	in	28.27×25.87×11.85	28.27×25.87×11.85	28.27×25.87×11.85	36.81×36.81×11.42
	Net/Gross Weight	lbs	31.9 / 38.6	31.9 / 38.6	31.9 / 38.6	51.8 / 59.5
Outdoor Side Noise Level			dB(A)	53	55	55
Outdoor Unit	Dimensions (WxDxH)	in	30.98×11.42×19.61	31.5×12.01×21.69	33.54×13.74×23.7	36.1×14.76×27.56
	Packing (WxDxH)	in	32.2×12.8×20.28	32.87×13.39×23.03	35.04×15.16×24.72	37.4×16.54×28.82
	Net/Gross Weight	lbs.	50.7 / 57.3	51.8 / 58.4	66.8 / 74.5	88.2 / 97.0
Refrigerant Type / Pre-charge			oz	R32 / 21.16	R32 / 20.46	R32 / 37.74
Refrigerant Precharge Length			ft	25	25	25
Refrigerant Piping	Liquid Side / Gas Side	in	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"
	Max Refrigerant Pipe Length	ft	49	49	65	65
Max Height Diff Between Indoor and Outdoor			ft.	33	33	49
Ambient Temperature Range	Cooling Indoor	°F	62~89	62~89	62~89	62~89
	Cooling Outdoor		5~127	5~127	5~127	5~127
	Heating Indoor		32~86	32~86	32~86	32~86
	Heating Outdoor		-4~75	-4~75	-4~75	-4~75





Up to 20.0 SEER2 Rating





Use your Smart device to
control your unit from
anywhere with
SMART APP!



SINGLE-ZONE

SLIM DUCT MINI SPLIT SYSTEM

9K, 12K, 18K & 24K Btu/h




Wall Thermostat included with Slim Duct Unit



16' Line Set and Drain Lines,
21' Communication Cable Included

Indoor Model			BRV-P09DT230VI	BRV-P12DT230VI	BRV-P18DT230VI	BRV-P24DT230VI
Outdoor Model			BRV-P09LS-230VO	BRV-P12LS-230VO	BRV-P18LS-230VO	BRV-P24LS-230VO
Power Supply		V-Ph-Hz	208~230-1-60	208~230-1-60	208~230-1-60	208~230-1-60
Cooling	Rated Capacity	Btu/h	9,000	12,000	18,000	24,000
	EER2	Btu/h	11.0	9.5	9.5	9.5
	SEER2	Btu/h	20.0	20.0	20.0	20.0
Heating	Rated Capacity	Btu/h	10,000	12,000	18,500	24,000
	HSPF2-4	Btu/h	9.5	9.5	9.5	9.5
	COP2	W/W	3.8	3.5	2.9	3.5
Minimum Circuit Ampacity		A	10	11	12	17
Max Fuse		A	15	15	20	25
Indoor Air Flow (Turbo/Hi/Mi/Lo/Mute)		CFM	335/305/276/182/182	360/330/270/217/194	500/426/370/300/283	741/623/558/529/470
Indoor Noise Level (Turbo/Hi/Mi/Lo/Mute)		dB(A)	42/39/34/28/28	42/39/34/28/28	48/44/41/36/33	51/49/46/39/34
Indoor Unit	Dimensions (WxDxH)	in	27.56×17.8×7.87	27.56×17.8×7.87	36.22×17.8×7.87	43.31×17.8×7.87
	Packing (WxDxH)	in	35.43×21.85×9.84	35.43×21.85×9.84	44.09×21.85×9.84	50.79×22.24×9.65
	Net/Gross Weight	lbs	33.1 / 39.7	33.1 / 39.7	39.7 / 47.4	50.7 / 58.4
Outdoor Side Noise Level		dB(A)	53	55	55	60
Outdoor Unit	Dimensions (WxDxH)	in	30.98×11.42×19.61	31.5×12.01×21.69	33.54×13.74×23.7	36.1×14.76×27.56
	Packing (WxDxH)	in	32.2×12.8×20.28	32.87×13.39×23.03	35.04×15.16×24.72	37.4×16.54×28.82
	Net/Gross Weight	lbs.	50.7 / 57.3	51.8 / 58.4	66.8 / 74.5	88.2 / 97.0
Refrigerant Type / Pre-charge		oz	R32 / 21.16	R32 / 20.46	R32 / 37.74	R32 / 42.33
Refrigerant Precharge Length		ft	25	25	25	25
Additional refrigerant charge >25ft.		oz/ft.	0.11	0.11	0.11	0.11
Refrigerant Piping	Liquid Side / Gas Side	in	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"
	Max Refrigerant Pipe Length	ft	49	49	65	65
Max Height Diff Between Indoor and Outdoor		ft.	33	33	49	49
Ambient Temperature Range	Cooling Indoor	°F	62~89	62~89	62~89	62~89
	Cooling Outdoor		5~127	5~127	5~127	5~127
	Heating Indoor		32~86	32~86	32~86	32~86
	Heating Outdoor		-4~75	-4~75	-4~75	-4~75



MULTI-ZONE

MINI SPLIT AIR CONDITIONING SYSTEM



Use your Smart device to
control your unit from
anywhere with SMART APP!


Outdoor Unit:

Outdoor Model			BRV-M18-230VO	BRV-M24-230VO	BRV-M30-230VO	BRV-M36-230VO	BRV-M42-230VO
Power Supply		V-Ph-Hz	208~230-1-60	208~230-1-60	208~230-1-60	208~230-1-60	208~230-1-60
Cooling	Rated Capacity (Min - Max)	Btu/h	17,700 (3,800-19,800)	24,000 (4,900-31,400)	30,000 (6,000-38,200)	36,000 (6,350~38,500)	42,000 (8,350-46,000)
	EER2	Btu/h	12.3	12.5	12.5	12.3	12.5
	SEER2	Btu/h	22	23	23	23	24
Heating	Rated Capacity (Min - Max)	Btu/h	18,000 (4,200-22,000)	24,000 (5,200-32,000)	30,000 (6,300-36,000)	36,000 (7,000~43,000)	42,000 (8,450-53,000)
	HSPF2-4	Btu/h	10	10	10	10	10.5
	COP2	W/W	3.8	4.0	3.9	4.0	3.9
Minimum Circuit Ampacity		A	20	30	40	45	45
Max Fuse		A	20	30	40	45	45
Outdoor Air Flow		CFM	1529	2235	2353	2353	4235
Outdoor Side Noise Level		dB(A)	54	57	58	59	60
Outdoor Unit	Dimensions (WxDxH)	in	34.65x13.90x21.93	38.58x15.28x27.56	41.18x17.91x31.81	41.18x17.91x31.81	39.80x15.75x51.97
	Packing (WxDxH)	in	35.55x15.04x24.21	39.96x16.73x30.00	43.50x19.49x34.84	43.50x19.49x34.84	42.52x16.93x56.69
	Net Weight	lbs.	75.0/80.5	102.5/109.1	148.8/157.6	154.3/163.1	205.0/224.9
Refrigerant Type / Volume		oz	R32/38.8	R32/51.2	R32/67.0	R32/81.2	R32/ 105.8
Refrigerant Precharge		ft	24.6	24.6	24.6	24.6	24.6
Refrigerant Piping	Liquid Side / Gas Side	in	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"
	Max Refrigerant Pipe Length	ft	82	82	82	82	82
Ambient Temperature	Outdoor (Cooling)	°F	-13~ 125.6	-13~ 125.6	-13~ 125.6	-13~ 125.6	-13~ 125.6
	Outdoor (Heating)	°F	-13~ 75.2	-13~ 75.2	-13~ 75.2	-13~ 75.2	-13~ 75.2

◇ Adapters for 1/4" / 1/2" and 1/4" / 5/8" included in box.



Up to 24.0 SEER2 Rating



Wall Mount:



Indoor Model			BRV-M07WM-230VI	BRV-M09WM-230VI	BRV-M12WM-230VI	BRV-M18WM-230VI	BRV-M24WM-230VI
Power Supply		V-Ph-Hz	208~230-1-60	208~230-1-60	208~230-1-60	208~230-1-60	208~230-1-60
Cooling	Rated Capacity	Btu/h	7,000	9,000	12,000	17,000	24,000
	Rated Capacity	Btu/h	7,000	9,000	12,300	17,700	24,000
Max Fuse		A	5	5	5	5	5
Indoor Air Flow		CFM	353	353	353	618	765
Indoor Noise Level		dB(A)	40	40	42	49	50
Indoor Unit	Dimensions (WxDxH)	in	31.02x7.80x11.50	31.02x7.80x11.50	34.49x7.64x11.73	38.82x8.86x12.40	44.13x9.09x12.95
	Packing (WxDxH)	in	34.65x14.57x11.42	34.65x14.57x11.42	37.99x14.57x11.1	42.13x15.16x12.28	47.64x15.75x12.87
	Net/Gross Weight	lbs.	17.60/22.00	17.60/22.00	19.80/24.27	26.45/32.26	33.07/39.68
Refrigerant Piping	Liquid Side / Gas Side	in	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	◇ 1/4" / 1/2"	◇ 1/4" / 5/8"
Operation Temperature Range		°F	60.8~89.6	60.8~89.6	60.8~89.6	60.8~89.6	60.8~89.6

◇ Adapters for 1/4" / 1/2" and 1/4" / 5/8" included in Outdoor Unit box.

Ceiling Cassette:



Indoor Model			BRV-M09CT-230VI	BRV-M12CT-230VI	BRV-M18CT-230VI	BRV-M24CT-230VI
Panel Model Number			BRV-PN9-18CT	BRV-PN9-18CT	BRV-PN9-18CT	BRV-PN24CT
Power Supply		V-Ph-Hz	208~230-1-60	208~230-1-60	208~230-1-60	208~230-1-60
Cooling	Rated Capacity	Btu/h	9,000	12,000	18,000	24,000
	Rated Capacity	Btu/h	10,000	12,000	18,500	24,000
Max Fuse		A	5	5	5	5
Indoor Air Flow		CFM	383	383	442	824
Indoor Noise Level		dB(A)	40	40	45	47
Indoor Unit	Dimensions (WxDxH)	in	22.44x22.44x10.24	22.44x22.44x10.24	22.44x22.44x10.24	33.07x33.07x9.69
	Packing (WxDxH)	in	28.35x25.59x11.42	28.35x25.59x11.42	28.35x25.59x11.42	35.83x35.83x12.20
	Net Weight	lbs.	30.9/37.5	30.9/37.5	33.1/38.6	52.9/61.7
Panel	Dimensions (WxDxH)	in	25.59x25.59x2.17	25.59x25.59x2.17	25.59x25.59x2.17	37.40x37.40x2.17
	Packing (WxDxH)	in	27.95x27.95x3.15	27.95x27.95x3.15	27.95x27.95x3.15	39.37x39.37x3.94
	Net/Gross Weight	lbs.	4.9/8.2	4.9/8.2	4.9/8.2	11.7/17.2
Refrigerant Piping	Liquid Side / Gas Side	in	1/4" / 3/8"	1/4" / 3/8"	◇ 1/4" / 1/2"	◇ 1/4" / 5/8"
Operation Temperature Range		°F	60.8~89.6	60.8~89.6	60.8~89.6	60.8~89.6

◇ Adapters for 1/4" / 1/2" and 1/4" / 5/8" included in Outdoor Unit box.

Ceiling Cassette Panel:



BRV-PN9-18CT

Panel Dimension:
25.59×25.59×2.17 in.
Panel Net Weight: 4.9 lb.



BRV-PN24CT

Panel Dimension:
37.40×37.40×2.17 in.
Panel Net Weight: 11.7 lb.

Slim Duct:



Indoor Model			BRV-M09DT-230VI	BRV-M12DT-230VI	BRV-M18DT-230VI	BRV-M24DT-230VI
Power Supply		V-Ph-Hz	208~230-1-60	208~230-1-60	208~230-1-60	208~230-1-60
Cooling	Rated Capacity	Btu/h	9,000	12,000	18,000	24,000
	Rated Capacity	Btu/h	10,000	12,000	19,000	24,600
Max Fuse		A	5	5	5	5
Indoor Air Flow		CFM	353	353	530	795
Indoor Noise Level		dB(A)	34	34	39	42
Indoor Unit	Dimensions (WxDxH)	in	27.56x17.72x7.8	27.56x17.72x7.8	27.56x27.56x9.65	39.37x27.56x9.65
	Packing (WxDxH)	in	34.25x21.3x10.24	34.25x21.3x10.24	36.61x32.68x11.81	48.43x32.68x11.81
	Net/Gross Weight	lbs.	27.6/33.1	27.6/33.1	47.4/56.2	59.5/70.5
Refrigerant Piping	Liquid Side / Gas Side	in	1/4" / 3/8"	1/4" / 3/8"	◇ 1/4" / 1/2"	◇ 1/4" / 5/8"
Operation Temperature Range		°F	60.8~89.6	60.8~89.6	60.8~89.6	60.8~89.6

◇ Adapters for 1/4" / 1/2" and 1/4" / 5/8" included in Outdoor Unit box.



Floor Ceiling:



Indoor Model			BRV-M09FC-230VI	BRV-M12FC-230VI	BRV-M18FC-230VI	BRV-M24FC-230VI
Power Supply		V-Ph-Hz	208~230-1-60	208~230-1-60	208~230-1-60	208~230-1-60
Cooling	Rated Capacity	Btu/h	9,000	12,000	18,000	24,000
	Rated Capacity	Btu/h	11,000	12,000	18,000	24,000
Max Fuse		A	5	5	5	5
Indoor Air Flow		CFM	500	500	530	824
Indoor Noise Level		dB(A)	39	39	41	44
Indoor Unit	Dimensions (WxDxH)	in	39.37×27.17×9.25	39.37×27.17×9.25	39.37×27.17×9.25	50.39×27.17×9.25
	Packing (WxDxH)	in	42.52×30.32×12.80	42.52×30.32×12.80	42.52×30.32×12.80	53.54×30.32×12.80
	Net/Gross Weight	lbs.	57.3/67.2	57.3/67.2	59.5/69.5	71.7/83.8
Refrigerant Piping	Liquid Side / Gas Side	in	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	1/4" / 5/8"
Operation Temperature Range		°F	60.8~89.6	60.8~89.6	60.8~89.6	60.8~89.6


◇ Adapters for 1/4" / 1/2" and 1/4" / 5/8" included in Outdoor Unit box.

Combination Chart:

Btu/h	Wall Mounted	Duct	Ceiling Cassette	Floor Ceiling
				
7K	BRV-M07WM-230VI			
9K	BRV-M09WM-230VI	BRV-M09DT-230VI	BRV-M09CT-230VI	BRV-M09FC-230VI
12K	BRV-M12WM-230VI	BRV-M12DT-230VI	BRV-M12CT-230VI	BRV-M12FC-230VI
18K	BRV-M18WM-230VI	BRV-M18DT-230VI	BRV-M18CT-230VI	BRV-M18FC-230VI
24K	BRV-M24WM-230VI	BRV-M24DT-230VI	BRV-M24CT-230VI	BRV-M24FC-230VI

			Cooling					Heating					Refrigerant	Refrigerant Piping						Ambient Temperature		
Model Name	Min. Circuit Ampacity (MCA)	Max. Fuse Size	Capacity (range)	Input	Rated current	SEER2	EER2	Capacity (range)	Input	Rated current	COP	HSPF	Noise Level	Type	Liquid side	Gas side	Max. length for all rooms	Max. length for one indoor unit	Max. height elevation between indoor and outdoor	Max. height elevation between indoor units	Cooling	Heating
	A	A	Btu/h	W	A			Btu/h	W	A			db (A)		inch	inch	ft	ft	ft	ft	°F	°F
BRV-M18-230VO	15	20	17,700(3,800-19,800)	1440	6.39	22	3.60	18,000(4,200-22,000)	1390	6.17	3.8	10	54	R32	2x1/4"	2x3/8"	131	82	49	33	-13~125.6	-13~75.2
BRV-M24-230VO	20	30	24,000(4,900-31,400)	1920	8.52	23	3.66	24,000(5,200-32,000)	1760	7.76	4.0	10	57	R32	3x1/4"	3x3/8"	197	98	49	33	-13~125.6	-13~75.2
BRV-M30-230VO	26	40	30,000(6,000-38,200)	2400	10.65	23	3.66	30,000(6,300-36,000)	2250	9.98	3.9	10	58	R32	4x1/4"	4x3/8"	263	115	49	33	-13~125.6	-13~75.2
BRV-M36-230VO	29	45	36,000(6,350~38,500)	2930	12.87	23	3.60	36,000(7,000~43,000)	2640	11.59	4.0	10	59	R32	4x1/4"	4x3/8"	263	115	49	33	-13~125.6	-13~75.2
BRV-M42-230VO	32	45	42,000 (8,350-46,000)	3360	14.92	24	3.66	42,000 (8,450-53,000)	3160	14.00	3.9	10.5	60	R32	4x1/4"	4x3/8"	263	115	49	33	-13~125.6	-13~75.2

UP TO 2 ZONES




BRV-M18-230VO

Note: 7K Wall Mount may be substituted for a 9K unit anywhere in this chart.

2 ZONES	
9K	9K
9K	12K
12K	12K

UP TO 3 ZONES




BRV-M24-230VO

2 ZONES		3 ZONES	
9K	9K	9K	9K
9K	12K	9K	12K
9K	18K	9K	18K
12K	12K	9K	12K
12K	18K	12K	12K
18K	18K		

Note: 7K Wall Mount may be substituted for a 9K unit anywhere in this chart.

UP TO 4 ZONES



BRV-M30-230VO

2 ZONES		3 ZONES		4 ZONES	
9K	9K	9K	9K	9K	9K
9K	12K	9K	12K	9K	12K
9K	18K	9K	18K	9K	18K
9K	24K	9K	24K	9K	18K
12K	12K	9K	12K	9K	12K
12K	18K	9K	12K	9K	12K
12K	24K	9K	12K	9K	12K
18K	18K	12K	12K		
18K	24K	12K	12K		

Note: 7K Wall Mount may be substituted for a 9K unit anywhere in this chart.



UP TO 4 ZONES



BRV-M36-230VO

2 ZONES	
9K	9K
9K	12K
9K	18K
9K	24K
12K	12K
12K	18K
12K	24K
18K	18K
18K	24K
24K	24K

3 ZONES		
9K	9K	9K
9K	9K	12K
9K	9K	18K
9K	9K	24K
9K	12K	12K
9K	12K	18K
9K	12K	24K
9K	18K	18K
9K	18K	24K
12K	12K	12K
12K	12K	18K
12K	12K	24K
12K	18K	18K
12K	18K	24K
18K	18K	18K

4 ZONES			
9K	9K	9K	9K
9K	9K	9K	12K
9K	9K	9K	18K
9K	9K	9K	24K
9K	9K	12K	12K
9K	9K	12K	18K
9K	9K	12K	24K
9K	9K	18K	18K
9K	9K	18K	18K
9K	12K	12K	12K
9K	12K	12K	18K
12K	12K	12K	12K
12K	12K	12K	18K

Note: 7K Wall Mount may be substituted for a 9K unit anywhere in this chart.

UP TO 5 ZONES



BRV-M42-230VO

2 ZONES	
9K	9K
9K	12K
9K	18K
9K	24K
12K	12K
12K	18K
12K	24K
18K	18K
18K	24K
24K	24K


3 ZONES		
9K	9K	9K
9K	9K	12K
9K	9K	18K
9K	9K	24K
9K	12K	12K
9K	12K	18K
9K	12K	24K
9K	18K	18K
9K	18K	24K
12K	12K	12K
12K	12K	18K
12K	12K	24K
12K	18K	18K
12K	18K	24K
18K	18K	24K

4 ZONES			
9K	9K	9K	9K
9K	9K	9K	12K
9K	9K	9K	18K
9K	9K	9K	24K
9K	9K	12K	12K
9K	9K	12K	18K
9K	9K	12K	24K
9K	9K	18K	18K
9K	9K	18K	24K
9K	12K	12K	12K
9K	12K	12K	18K
9K	12K	12K	24K
9K	12K	18K	18K
9K	12K	18K	24K
12K	12K	12K	12K
12K	12K	12K	18K
12K	12K	12K	24K
12K	12K	18K	18K
12K	12K	18K	24K

5 ZONES				
9K	9K	9K	9K	9K
9K	9K	9K	9K	12K
9K	9K	9K	9K	18K
9K	9K	9K	9K	24K
9K	9K	9K	12K	12K
9K	9K	9K	12K	18K
9K	9K	9K	12K	24K
9K	9K	9K	18K	18K
9K	9K	9K	18K	24K
9K	9K	12K	12K	12K
9K	9K	12K	12K	18K
9K	9K	12K	12K	24K
9K	9K	12K	18K	18K
9K	9K	12K	18K	24K
12K	12K	12K	12K	12K
12K	12K	12K	12K	18K
12K	12K	12K	12K	24K
12K	12K	12K	18K	18K
12K	12K	12K	18K	24K



DOWNLOAD THE BRAVO REMOTE APP



- Remote Control Included for all units.
- Wall Thermostat Included except for Wall Units.

Scan the following intelligent QR code to download SMART APP for iOS or Android

The logo for Bravo, featuring the word "Bravo" in a green serif font. The letter "v" is replaced by a red checkmark that extends upwards and to the right.

Bravo

MORE THAN A COMPLIMENT

08202026